

**DECLARATION OF PERFORMANCE**  
**according to Regulation (EU) 305/2011**  
**No. 1015-CPR-30-17512/TZ**

- |    |   |   |
|----|---|---|
| 1  | Unique identification code of the product-type:   | Room heaters fired by wood fuel without hot water supply<br><b>MAGIC ECO</b>  |
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):                  | Serial No (see rating label on the product): 0002   |
| 3. | Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: | Appliance with intermittent and continues burning regime for operation with closed doors  |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):                        | <b>TIM SISTEM d.o.o.</b><br>Prva Industrijska str.No.9, Industrial area Nova Pazova<br>22 330 Nova Pazova, Serbia, <b>e-mail:</b> office@timsistem.rs |
| 5. | Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):                 | -   |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:                         | System 3  |
| 7. | In case of the declaration of performance concerning a construction product covered by a harmonized standard:   | <b>Strojirenský zkušební ústav, s.p</b><br>Hudcova 424/56b, Medlánky, 621 00 Brno, Česká republika<br>Body ID : 1015 , Test report :30-17512/T        |

8. Declared performance:

Harmonized technical specification	EN 16510-2-1:2022
Essential characteristics	Performance
<b>Fire safety</b>	
Reaction to fire	A1
Distance to combustible materials	Minimum distance, in mm sides = 350, rear = 450, front = 1000
Risk of burning fuel falling out	Pass
Emission of combustion products at nominal heat output, in mg/m3 at 13% O2	CO 28
	Dust 35
	NOx 114
	CxHy 24
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Clean ability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T [270 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
<b>Thermal output</b>	
Nominal heat output	6,90 kW
Room heating output	- kW
Water heating output	- kW
Energy efficiency	$\eta$ 78,1 %

07.02.2025.



Ivan Stankovic, CEO